

## Cautions & Ckeck list



www.dh34.com

# DFS·2S

DAEHAN SENSOR CO.,LTD.

Head Office : 133-849, 94-2, Yongdap-dong Sungdong-gu Seoul Korea  
 Factory : 467-8/31, 275-1 Dorip-ri Baeksa-myeon Icheon-shi Gyeonggi-do Korea  
 R&D Center : 130-846, 2-71 Jeonnong-dong Dongdaemun-gu Seoul Korea  
 Tel : 82-2-2213-9888 Fax : 82-2-2245-3482

DAEHAN SENSOR

## Product Description

## 제품 사양

## 제품 치수

When a certain amount of liquid flows inside pipe, the paddle of flow switch which installed inside pipe moves and it affects reed switch which activates on/off the related pump and/or alarm.

**Application : Liquid only**

**Wiring : 2 Wire**  
(Input/Output The same)

**Ouytput type : Reed Switch**  
(SPST)

**Supply voltage : AC 220V 1A**

**Process Temperature : 0℃ ~ 80℃**

**Process Pressure : Max. 10Kg/cm<sup>2</sup>**

**Material : Socket - SUS304**  
**Bolt - SUS 304**  
**Shaft - SUS304**  
**Paddle - SUS304**

## Features

- Excellence in durability (Semipermanent)
- Due to the small size, the proudct can be installed in a narrow space around plumbing.
- Reed switch with relay output.

